

DESCRIPTION

- **LubeRite EPG** is a premium quality, lithium-type grease containing an extreme pressure agent and oxidation and rust inhibitors.

APPLICATIONS

- Highly recommended for grease applications where high and shock loads are encountered.
- Centralized grease lubrication systems such as in steel mills or cement factories; also suitable for ball and roller bearings under high load conditions.
- Applicable in high pressure conditions where machine elements are moving in low speed or in oscillating motion.

PROPERTIES

- Applicable at high or low temperatures
- Good water resistance
- Excellent oxidation and thermal stability
- Excellent pumpability

TYPE

- Lithium-based extreme pressure grease

GRADES

- NLGI Nos. 1, 2, 3, 0 and 00

AVAILABLE PACKAGES

- 400-lb (181-kg) drum
- 35-lb (16-kg) pail

TYPICAL CHARACTERISTICS

	EPG 1	EPG 2	EPG 3	EPG 0	EPG 00
Appearance	Uniform	Uniform	Uniform	Uniform	Uniform
Texture	Smooth	Smooth	Smooth	Smooth	Smooth
Color, Visual	Gray	Gray	Gray	Gray	Gray
Worked Pen. At 25°C, mm/10					
60 Strokes	320	283	238	358	420
10,000 Strokes	327	290	245	372	427
Dropping Point, °C	182	182	180	182	182
Base Oil Viscosity, cSt at 40°C	200	200	96	115	25
Tilted Wheel Bearing Test					
Slump Rating	Passes	Passes	Passes	Passes	Passes
Leakage, grams	0.5	0.5	0.1	3.5	3.5
Oxidation Stability, psi	5	5	5	5	5