

ISOTECT HC2

ISOTECT HC2 is a low-viscous, water immiscible, corrosion protection fluid especially for interstratification and for short transports demanding medium corrosion protection.

ISOTECT HC2 is suitable for cutting and forming operations on steel (up to approx. 1.5 mm). Especially, if corrosion protection for both storage and transport is required. ISOTECT HC2 can even be used on complicated parts. They are effectively protected against corrosion.

ISOTECT HC2 also keeps its rust preventing properties if the parts are touched, i.e. sour hand perspiration is neutralized.

ISOTECT HC2 can easily be used for all metal combinations. Metal-resistant seals, packing and hoses can be wetted with ISOTECT HC2 without further ado.

ISOTECT HC2 is free from organic chlorine compositions and does neither contain PCB, PCT nor phenol.

Chemical and physical data:

Colour		: brown
Density/20°C	DIN 51 757	: 0.841g/cm ³
Viscosity/20°C	DIN 51 562	: approx. 10.0mm ² /s
Flash point	DIN 51 758	: 137°C
Pour point	ISO 3 016	: approx.-1°C

Handling:

ISOTECT HC2 should not be used in temperatures of less than 0°C

Protection: Short to Medium Term

Packing: Steel Drum

Net Weight: 160 kg/Drum

Only valid in combination with EC-Safety-Data-Sheet.

Warranty

The information given here is considered to be correct and is offered for your consideration, investigation and verification. No warranties are expressed or implied since the use of our products is beyond our control. Statements concerning the use of PETROFER-products are not to be constructed as recommending the infringement of any patent.