

ISOLUBE 4683

ISOLUBE 4683 is a special drawing oil which has been developed for extremely demanding drawing operations on aluminium. The product is based on mineral oil. By using ISOLUBE 4683 it is possible to draw at a much higher speed than normal. Despite of the increased drawing speed maximum surface qualities will be achieved due to the highly effective additives in ISOLUBE 4683 which reduce the friction between the material and the tool.

Even in case of increasing darkening of the material which naturally occurs because of fine-disperse aluminium abrasives, ISOLUBE 4683 works without any problems. That means, that even after a prolonged use of the product the drawing operation and thus the wire quality will remain as good as in the beginning.

Physical Data:

Appearance	yellow-brown	
Spec. Gravity at 20°C	0.890(g/cm ³)	DIN51 757
Viscosity at 40°C	ca.155mm ² /S	DIN51 562
Flash Point (°C)	180	ISO 2 592
Pour Point (°C)	+ 5	ISO3 016
	0.002	DIN 51 575
Average values.		

Packing:

Steel Drum(208 Liters)
Netweight:180Kg/Drum

Only valid in combination with EC-Safety-Data-Sheet.

Warranty

The information given here is considered to be correct and is offered for your consideration, investigation and verification. No warranties are expressed or implied since the use of our products is beyond our control. Statements concerning the use of PETROFER-products are not to be constructed as recommending the infringement of any patent.

16.06.2011

Page 1/1